

Unbreakable bonds

start here.



About Us

At Swellco Chemical we are dedicated to providing tailored solutions for all your Adhesive requirements. As a trusted Chemical manufacturer, we take pride in our craftsmanship, offering an extensive range of high-quality Adhesive for various applications. Whether you seek timeless elegance for residential spaces or durable solutions for commercial projects, our diverse collection caters to your unique style. With a focus on sustainability and expert guidance, we aim to elevate your spaces with our exquisite Chemical. Partner with us and discover the art of transforming your surroundings with beauty and sophistication.

Index

| | |
|-----------------------|----|
| Tile Grout | 01 |
| Grout Hardner | 02 |
| Epoxy Grout | 03 |
| Adhesives | 04 |
| Block Adhesives | 05 |
| Tiles Cleaner | 06 |
| Tiles Leveler | 07 |
| Tiles Spacer | 08 |
| SS Trowel | 09 |

TILES GROUT



The latest for Wall & Floor tiles Joints with polymer-modified grout

* Application Area

Wall, Floors, Indoors & Outdoors
Dry Areas, Work Tops

* Coverage

Consumption Depend on
joint width, size of Tiles and Good
Workmanship.

Available in
1 kg



Water
Resistant



UV
Resistance



Chemical
resistance

* Technical Information

| Parameters | Pot life @ 30c, minutes | Open time, minutes 30 | Adjustability, minutes | Initial Set & Rt, Hours | Final Set #RT, Hours | Shrinkage, % |
|------------|-------------------------|-----------------------|------------------------|-------------------------|----------------------|--------------|
| Results | 60 | 30 | 15-20 | 2 | 8 | <0.1 |

GROUT ADMIXTURE



Primarily Used to make paste of tiles grout, it can be used with variety of grouts

* Application Area

Used with all types of cement grouts

* Coverage

Consumption depend on joint width, size of tiles and good workmanship

Available in

Packing 250ML & 400 ML



Water
Resistant



UV
Resitance




Chemical
resistance

* Technical Information

| Parameters | Physical Appearance | Specific gravity | Solid Contain | Odour |
|------------|---------------------|------------------|---------------|--------|
| Results | White Liquid | 0.955 | 20.5% | Medium |

NSA STANDARD



* Product Details

Interior Wall & Floor Tile Adhesive

* Application Areas

Use for Ceramic Floor Tiles & Wall Tiles On Floor & Wall, Use For Vitrified Tiles and Porcelain On Floor

* Coverage

Approximately 4.5 to 5m²/20kg
@3mm thickness when using a thin trowel

Available in

Packing 20kg | Grey Color



Water
Resistant



UV
Resistance



Chemical
resistance

* Technical Information

| Properties | Results |
|--|-----------------------|
| Apperance | Free Flowing Powder |
| Color | Grey |
| Prolife | 3 Hours |
| Open time | 35 Min |
| Adjustability | 25 min |
| Trafficable time , Hrs | 24 |
| Shear Adhesion, Dry Condition (As Per Annex B) | 1.09N/MM ² |
| Tensile Adhesion, (As Per Annex A) | 1.0N/MM ² |

NSA Premium



* Product Details

Interior for wall & vitrified tiles adhesive, tiles-on-tile, window framing. Application Areas Use for Applying ceramic tiles on wall vitrified tiles on wall up to 600 X1200 mm & floor. porcelain Tiles, window Framing Tiles on Tiles on floor

* Coverage

Approximately 4.5 to 5m²/20kg
@3mm thickness when using a thin trowel

Available in

Packing 20kg | Grey Color



* Technical Information

| Properties | Results |
|--|-------------------------|
| Apperance | Free Flowing Powder |
| Color | Grey |
| Prolife | 3 Hours |
| Open time | 35 Min |
| Adjustability | 25 min |
| Trafficable time , Hrs | 24 |
| Shear Adhesion, Dry Condition (As Per Annex B) | |
| Dry Condition | >1.22 N/MM ² |
| Heat Condition | >1.10 N/MM ² |
| Wet Condition | >1.10 N/MM ² |
| Tensile Adhesion, (As Per Annex A) | |
| Dry Condition | >1.10 N/MM ² |
| Wet Condition | >1.00 N/MM ² |

NSA LUXURIOUS GREY & WHITE



Wall And Vitrified Interior & Exterior
tiles adhesive

* Application Area

Applying tile on tile wall and floor,
Applying vitrified tiles on wall internal
& Externally (600X600mm, 800X800
mm, 600X1200mm), Applying wind-
ow seal & door granites.

* Coverage

Approximately 4.5 to 5m²/20kg
@3mm thickness when using a thin trowel

Available in

Packing 20kg | Grey Color



Water
Resistant



UV
Resistance




Chemical
resistance

* Technical Information

| Properties | Results |
|--|-------------------------|
| Apperance | Free Flowing Powder |
| Color | White & Grey |
| Prolife | 3 Hours |
| Open time | 35 Min |
| Adjustability | 25 min |
| Trafficable time , Hrs | 24 |
| Shear Adhesion, Dry Condition (As Per Annex B) | |
| Dry Condition | >1.50 N/MM ² |
| Heat Condition | >1.20 N/MM ² |
| Wet Condition | >1.10 N/MM ² |
| Tensile Adhesion, (As Per Annex A) | |
| Dry Condition | >1.40 N/MM ² |
| Wet Condition | >1.10 N/MM ² |

NSA SUPERB GREY & WHITE



Interior & Exterior Wall & Floor Tiles
marble, Italian marble & stone adhesive, all kinds of tile on tile

* Application Area

Use for low and high water absorption surfaces use for applying of big size vitrified & porcelain tiles internally and externally. use for app- lying of low water absorption tiles such as single fired tiles, natural stone marbles etc.

* Coverage

Approximately 4.5 to 5m²/20kg
@3mm thickness when using a thin trowel

Available in

Packing 20kg | White-Grey Color



* Technical Information

| Properties | Results |
|--|-------------------------|
| Apperance | Free Flowing Powder |
| Color | White & Grey |
| Prolife | 3 Hours |
| Open time | 35 Min |
| Adjustability | 25 min |
| Trafficable time , Hrs | 24 |
| Shear Adhesion, Dry Condition (As Per Annex B) | |
| Dry Condition | >1.55 N/MM ² |
| Heat Condition | >1.30 N/MM ² |
| Wet Condition | >1.15 N/MM ² |
| Tensile Adhesion, (As Per Annex A) | |
| Dry Condition | >1.60 N/MM ² |
| Wet Condition | >1.20 N/MM ² |
| Deformability (As Per Annex B) | >2.60MM |

ACC BLOCK ADHESIVE



HIGH ADHESION OF FLY ASH BLOCK

* Application Area

Used Of Fly Ash Block
Adhesion

* Coverage

Depends Upon the Soze of Block & Good Craft
Man Ship

Available in
Packing 40kg.



* Technical Information

| Properties | Results |
|--|-----------------------|
| Apperance | Free Flowing Powder |
| Color | Grey |
| Prolife | 3 Hours |
| Open time | 35 Min |
| Adjustability | 25 min |
| Trafficable time , Hrs | 24 |
| Shear Adhesion, Dry Condition (As Per Annex B) | 1.09N/MM ² |
| Tensile Adhesion, (As Per Annex A) | 1.0N/MM ² |

EPOXY GROUT

JOINT FILLER (THREE PACK & TWO PACK)



Hydrotherapy Pools

The latest for wall & floor tiles joints with hardener & resin based grouts
special availability of glitter along with nonglitter
(EASE OF APPLICATION AND CLEANING)

* Application Area

Walls | Floors | Indoor & Outdoor | Dry & Wet Areas | Work tops |
Showers area | Swimming Pools| Heavily trafficked floors |
Hygienic sterile chemical resistance areas |

* Coverage

Consumption Depend on joint width,
size of Tiles and Good Workmanship.

Available in
Packing 1kg & 5 kg



Water
Resistant



UV
Resistance



Chemical
resistance

* Technical Information

| Parameters | Shear Adhesion Strength | Abrasion Resistance | Mechanical Flexural Strength | Compressive Strength | Water Absorption |
|------------|-------------------------|-----------------------|------------------------------|----------------------|------------------|
| Results | >2N/M ² | =250n/mm ³ | =30N/mm ² | =45N/mm ² | Nil (1) |

| Properties | Tensile Adhesion (14 Days air) | Epoxy Grout | Epoxy Grout |
|------------|--------------------------------|-------------------------|-------------------------|
| Results | 24 | >4.5 Dry Condition (KN) | >3.6 Dry Condition (KN) |

Tiles Cleaner



Fast Acting Wall & Floor Tiles Cleaner

* Application Area

Wall, Floors, Interiors, Exteriors, Day & wet Areas
Showers, Swimming Pool

* Note

Do not use on surfaces that are not resistant to acid such as marble/terrazzo. Do not use your bare hand, use hand gloves while using of tiles care. Highly reactive to skin.

Available in
Packing 500ML & 1 Ltr



Tiles Leveler

Tiles Leveling
And Equalizing Surface

* Application Areas

Wall | Floors | Interiors | Exteriors | Dry & Wet areas |
Showers | Swimming Pools

* Packing Details

50(Clip)+50(wedge) Other Clips

* Available In

1.5, 2, 3 & 4 mm Thickness.

Demand Quantity (Clip/M)²

| Area Size | 1 ² m | 2 ² m | 5 ² m | 10 ² m | 20 ² m | 50 ² m |
|--------------|------------------|------------------|------------------|-------------------|-------------------|-------------------|
| 30x30 cm | 12 | 24 | 60 | 120 | 240 | 600 |
| 40x40 cm | 25 | 50 | 125 | 250 | 500 | 1250 |
| 50x50 cm | 15 | 30 | 75 | 150 | 300 | 750 |
| 30x60 cm | 18 | 36 | 90 | 180 | 360 | 900 |
| 60x60 cm | 12 | 20 | 50 | 100 | 200 | 500 |
| 80x80 cm | 10 | 20 | 45 | 80 | 140 | 360 |

Tiles Spacer

For consistent and even spacing of tiles.

* Application Areas

Wall | Floors | Interiors | Exteriors | Dry & Wet areas | Showers | Swimming Pools

* Available Size

2mm, 3mm, 4mm, 5mm, 6mm, 8mm, 10mm

* Pack Size :

100Nos. Per Packet

Demand Quantity (Clip/M)²

| Area Size | 1 ^m | 2 ^m | 5 ^m | 10 ^m | 20 ^m | 50 ^m |
|--------------|----------------|----------------|----------------|-----------------|-----------------|-----------------|
| 30x30 cm | 12 | 24 | 60 | 120 | 240 | 600 |
| 40x40 cm | 25 | 50 | 125 | 250 | 500 | 1250 |
| 50x50 cm | 15 | 30 | 75 | 150 | 300 | 750 |
| 30x60 cm | 18 | 36 | 90 | 180 | 360 | 900 |
| 60x60 cm | 12 | 20 | 50 | 100 | 200 | 500 |
| 80x80 cm | 10 | 20 | 45 | 80 | 140 | 360 |



S S TROWEL

* Tiles Spacer

For consistent and even spacing of tiles.

* Product

while using thin-set adhesives to fix tiles and stones, a notched trowel plays a vital role.

* Applications


If you use notch trowel while using thin-set adhesives you can avoid such as hollow sounds, cracks, chipping of tiles, lippage and de-bonding of tiles.

* PACKING

LOOSE PIC

EPOXY GROUT


AVAILABLE COLOUR




001 Bright
White




002 Quarry
Red




003 Silk
(ivory)



004
Almond



007
Dusty Rose



008
Parchment



011
Sandstone




013
Midnight Black




014
Mocha




016
Burgundy



017
Light Green



018
Silver Shadow



019
State Grey



020
Natural Grey



022
Platinum



023 Raven




025
Crayon Red



026
Mayan Red




027
Sable




028 Hemp



029 Ivy




030
Sierra Sunrise




031
Inca Gold



032 Sage




033 Saltillo




034 Aqua Blue




035 Sapphire



038
Spectra Pink




039
Lemon Yellow




042
Italian Tera
Cotta

EPOXY GROUT


AVAILABLE COLOUR



Bright White




Quarry Red



Silk




Midnight Black




Sky Blue




Mocha




Lemon Yellow




Sand Stone




Burgandy




Silver Shadow



Slate Grey



Natural Grey




Platinum




Raven



Sable




Sierra Sunrise




Inca Gold



Sapphire



Cadmimum
Red




Spectra Pink


- * 3 Part & 2 Part epoxy same colour available in sparkle
- * Silver series
- * Gold Series
- * Copper Series

TILES GROUT


AVAILABLE COLOUR




White




Ivory




Grey




T.Blue




Pink




Magenta




B.Beige



Jesalmer




Bottle Green




Sor.Blue



c.Brown



R.Brown



Terracotta



Black

Tiles Adhesive Details

| SR.NO | PRODUCT | GREAD | PACK | APPLICATION AREA |
|-------|------------------------|-------|------|---|
| 1 | NSA STANDARD ADHESIVE | GREY | 20KG | Applying ceramic wall tiles on wall internally, Applying vitrified tiles on floor (600X600mm, 600X1200mm,800X800mm, 800X1200mm,) Applying floor tiles on floor (300X300mm, 400X400mm) |
| 2 | NSA STANDARD ADHESIVE | WHITE | 20KG | Applying ceramic wall tiles on wall Externally, Applying vitrified tiles on floor (600X600mm, 600X1200mm,800X800mm, 800X1200mm,) Applying floor tiles on floor (300X300mm, 400X400mm) |
| 3 | NSA PREMIUM ADHESIVE | GREY | 20KG | Applying tile on tile on floor, applying vitrified tiles on wall internally (600X600mm,600X1200mm,800 X800mm) Applying window & door granites. |
| 4 | NSA PREMIUM ADHESIVE | WHITE | 20KG | Applying tile on tile on floor, applying vitrified tiles on wall Externally (600X600mm,600X1200mm,800 X800mm) Applying window & door granites. |
| 5 | NSA LUXURIOUS ADHESIVE | GREY | 20KG | Applying tile on tile wall and floor, Applying vitrified tiles on wall internally (600X600mm, 800X800mm, 800X1200mm) Applying window & door granites. |
| 6 | NSA LUXURIOUS ADHESIVE | WHITE | 20KG | Applying tile on tile wall and floor, Applying vitrified tiles on wall Externally (600X600mm, 800X800mm, 800X1200mm) Applying window & door granites. |
| 7 | NSA SUPERB ADHESIVE | GREY | 20KG | Applying Vitrified slabs wall internally (1000X1000mm, 1200X2400mm, 750X1500mm,800X2400mm,1600X3200 mm), Applying Vitrifide Tile On Wall Internally (600X 600mm,1000X1000mm) Applying natural stone, marble & granites on Wall internally |
| 8 | NSA SUPERB ADHESIVE | WHITE | 20KG | Applying Vitrified slabs wall Externally (1000X1000mm, 1200X2400mm, 750X1500mm,800X2400mm,1600X3200 mm), Applying Vitrifide Tile On Wall Externally (600X 600mm,1000X1000mm) Applying natural stone, marble & granites on Wall internally |
| 9 | BLOCK ADHESIVE | GREY | 20KG | For applying light weight aac block adhesive |

